

NESTE OIL

NESTE HYPOIDI S

Fully Synthetic transmission and drive gear oil

SAE 75W-90 and 75W-140

API GL-5

MIL-L-2105 D

Scania STO:1 (75W-140)

Neste Hypoidi S grades are made of a fully synthetic base oil mixed with extreme-pressure, oxidation and rust resistance additives. Good operation properties at severe below-zero temperatures and low friction drag, which make for good fuel economy, are special features of these oils.

TYPICAL CHARACTERISTICS	75W-90	75W-140
Densitykg/m ³ 15°C	886	857
Flash Point°C (COC)	222	220
Pour Point°C	-54	-48
Viscosity Index	180	181
ViscositycSt/ 40 °C	86	172
ViscositycSt/ 100 °C	14,7	25
Brookfield Viscosity cP/ -40 °C	29800	111000
Tunnelling point °C	-55	<-45

Neste Hypoidi S 75W-90 is recommended for an API GL-5 class transmission and drive gear oil in passenger cars and vans. Neste Hypoidi S 75W-140 for heavy-duty transportation - both can befor year-round use. They can be blended with ordinary gear oils if necessary and they do not damage the gaskets.

Neste Hypoidi S 75W-140 fills Scania STO:1 requirements and is suitable for Scania drive gears especially in cold climate conditions.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 10 45 85410
Updated 13.12.2011 0:00:00

Print

Close
