

Vehicle Diagnostic Report

1999 RX300 1MZ-FE

1

Printed By: Default User(1)

09.06.2025 21:06:30

Data List Engine and ECT(1 of 2)

Time/Frame : 33:48:484/1

Parameter	Value	Unit
Injector	3,0	ms
IGN Advance	15,0	deg
IAC Duty Ratio	41,4	%
CALC Load	14,90	%
MAF	3,14	gm/sec
Engine SPD	705	rpm
Coolant Temp	208	F
Intake Air	108	F
Throttle POS	12	%
IDL SIG	ON	
Vehicle SPD	0	MPH
O2S B1 S2	0,005	V
AFS B1 S1	3,325	V
AFS B2 S1	3,300	V
Short FT #1	5,43	%
Long FT #1	21,83	%
TOTAL FT #1	1,012	
Short FT #2	-0,04	%
Long FT #2	10,12	%
O2FT B1 S2	99,15	%
AF FT B1 S1	4,65	%
AF FT B2 S1	-0,04	%
FUEL SYS #1	CL	
FUEL SYS #2	OLDRIVE	
FC IDL	OFF	
MIL Status	ON	
Starter SIG	OFF	
A/C SIG	OFF	
PNP SW	ON	
Elect Load SIG	OFF	
Stop Light SW	OFF	
PS Oil Press SW	OFF	
PS Signal	ON	
Intake CTL VSV1	OFF	
Intake CTL VSV2	OFF	
Fuel Pump	ON/H	
A/C MAG Clutch	OFF	
EVAP VSV	OFF	
Vapor Press VSV	ON	
VVT CTRL B2	OFF	
VVT CTRL B1	ON	
Shift	1st	
Overdrive Cut SW1	OFF	
Overdrive Cut SW2	OFF	
ECT power mode / M SW	OFF	
Reverse	OFF	
4th(M)/Drive	OFF	
2nd	OFF	
Low	OFF	
IGNITION	1413	
Cylinder #1 Misfire Count	0	
Cylinder #2 Misfire Count	0	
Cylinder #3 Misfire Count	0	
Cylinder #4 Misfire Count	0	
Cylinder #5 Misfire Count	0	
Cylinder #6 Misfire Count	0	

Parameter	Value	Unit
Cylinder #7 Misfire Count	0	
Cylinder #8 Misfire Count	0	
MISFIRE RPM	0	rpm
MISFIRE LOAD	0,00	g/rev
FC TAU	OFF	
# Codes	2	
Check Mode	OFF	
AS Test	COMPL	
OXS2 Test	COMPL	
OXS1 Test	COMPL	
SPD (NT)	650	rpm
AT Fluid Temp	176	F